


## **Experience the DEL Difference**

## **Specifications**

- Up to 120 containers per minute
- Dual-timing screw in-feed
- Vacuum-film waste removal system
- Stainless steel (non-wash down) construction
- Mechanical container diameter adjustment
- Ethernet and communications modules
- Vacuum-film transfer technology
- Variable speed capability without affecting heat-seal
- Servo-controlled rotary-die and vacuum transfer system for membrane
- 460 Volt / 60 Hertz / 3 Phase NEMA 12 DC Electrical

## **Available Options**

- Wash-down design
- Soft-reject (film-splice and offset-seal detection)
- Leak detection (Gross to Micro Leaks)
- Modified atmosphere packaging (nitrogen gassing)
- Laser-print capabilities for seal-head identification
- All domestic and international voltages to meet UL and CE requirements)



ELECTRICAL DROP 460VAC,3PH,60HZ, (AMPERAGE PENDING)

LOW VOLTAGE PANEL


6"x12' TABLETOP INDEXING CONVEYOR

GH VOLTAGE PANEL -AIR DROP: 16 CFM @ 40 PSI

TIMING SCREW

6"x7' TABLETOP

AIR DROP: 10 CFM @ 80 PSI



## **Contact DEL Packaging, Ltd**

18113 Telge Road | Cypress, TX 77429

Phone: 281.653.0099 | Fax: 281.653.0082

http://www.delpackaging.com | sales@delpackaging.com



SHUTTLE PLATE

CRADLE BLOCK ASSY

HEIGHT ADJUSTMENT HANDLE

